



## MATERIAL SAFETY DATA SHEET

### SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME	DIMENSION		
PRODUCT CODE	SEA16886	MANUFACTURER	TEAM SYSTEMS
ISSUE DATE		STREET ADDRESS	6325 Hurst Street
SUPERCEDES	06/22/01	CITY, STATE ZIP	Houston, Texas 77008
		PHONE	(713) 868-1461

**EMERGENCY TELEPHONE NUMBER**  
1-800-535-5053

### SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS No.	OSHA PEL/TLV	EXPOSURE LIMITS		OTHER LIMITS
			ACGIH TLV	STEL	
Butoxyethanol	111-76-2	25 ppm	25 ppm	Not applicable	None
Nonylphenoethoxylate	9016-45-9	NE	NE	NE	NA
Dipropylene Glycol Methyl Ether	34590-94-8	100ppm	100ppm	150ppm	100ppm
Ethylene Glycol	107-21-1	50ppm	50ppm	NA	NA

### SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	May produce eye, skin, and gastrointestinal irritation.
--------------------	---

POTENTIAL HEALTH EFFECTS	
INGESTION .....	Irritation and central nervous system effects as noted in Section 11.
INHALATION .....	Irritation and central nervous system effects as noted in Section 11.
EYE CONTACT .....	Burns
SKIN CONTACT .....	Irritation, defatting of skin.

### SECTION 4 – FIRST AID MEASURES

INGESTION	Drink large quantities of water. DO NOT INDUCE VOMITING. <b>See a physician immediately.</b>
INHALATION	Remove victim to fresh air. Do not return until mists have dissipated.
EYE CONTACT	Flush with water for 15 minutes while holding lids open. <b>See a physician.</b>
SKIN CONTACT	Flush with water. Remove contaminated clothing and do not re-wear until washed. If irritation persists, see a physician.
NOTE TO PHYSICIAN	Treatment based on judgment of the physician in response to reactions of the patient.



**SECTION 5 – FIRE FIGHTING MEASURES**

FLASH POINT / METHOD	>200F	FLAMMABLE LIMITS	None
% VOLATILE	NA		
EXTINGUISHING MEDIA	Dry chemical, water mist, alcohol foam		
SPECIAL FIRE FIGHTING PROCEDURES	Firefighters should wear a self-contained breathing apparatus as in all chemical fires.		
FIRE AND EXPLOSION HAZARDS	None		

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

RESPONSE TO SPILLS	Stop leak. Dilute spilled material with large amounts of water.
--------------------	---

**SECTION 7 – HANDLING AND STORAGE**

HANDLING PRECAUTIONS	Wash hands before eating. Keep container tightly closed when not in use.
STORAGE PRECAUTIONS	Store in a cool, dry place.

**SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTIONS**

HYGIENIC PRACTICES	Normal procedures for good hygiene. Observe label precautions. Use personal protection equipment.
ENGINEERING CONTROLS	Use general mechanical ventilation to remove vapors at the source. Eyewash station is recommended.

	<b>RESPIRATOR</b>	Not necessary
X	<b>GOGGLES / FACE SHIELD</b>	Required-goggles should be chemical splash type
	<b>APRON</b>	Not necessary
X	<b>GLOVES</b>	Required; chemical resistant type
	<b>BOOTS</b>	Not necessary

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Light Blue	BOILING POINT	> 212° F
ODOR	Solvent	VAPOR PRESSURE	ND
pH	8.5	VAPOR DENSITY	ND
SPECIFIC GRAVITY	1.015	EVAPORATION RATE (butyl acetate=1)	<1
SOLUBILITY IN WATER	ND		



**SECTION 10 – STABILITY AND REACTIVITY**

CHEMICAL STABILITY		STABLE	X		UNSTABLE	
CONDITIONS TO AVOID	Elevated temperatures					
INCOMPATIBILITY	Strong acids and oxidizing agents					
HAZARDOUS PRODUCTS OF DECOMPOSITION	None					
POLYMERIZATION		WILL NOT OCCUR	X		MAY OCCUR	
CONDITIONS TO AVOID	None					

**SECTION 11 – TOXICOLOGICAL INFORMATION****CARCINOGENICITY**

	THIS PRODUCT CONTAINS A KNOWN OR SUSPECTED CARCINOGEN
X	THIS PRODUCT DOES NOT CONTAIN ANY KNOWN OR ANTICIPATED CARCINOGENS ACCORDING TO THE CRITERIA OF THE NTP ANNUAL REPORT ON CARCINOGENS AND OSHA 29 CFR 1910,Z

**OTHER EFFECTS**

ACUTE	Central nervous system depression, headache, nausea, dizziness, and coughing. Sever irritation to eyes and will defat skin on repeated and prolonged contact.
CHRONIC	Chronic exposure to butoxyethanol may cause damage to the liver, kidney, and blood forming organs.
ORAL LD/50	Unknown

**SECTION 12 – DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL	Diluted material may be flushed to sewer.
----------------	---

**SECTION 13 – TRANSPORT INFORMATION**

DOT CLASSIFICATION		HAZARDOUS			NOT HAZARDOUS	X
DESCRIPTION	NA					
SEATEX HM CODE	000					

**SECTION 14 – OTHER INFORMATION****HMIS CLASSIFICATION**

1	BLUE	HEALTH HAZARD
0	RED	FLAMMABILITY
0	YELLOW	REACTIVITY
Alk	WHITE	SPECIAL HAZARD

Information contained in this MSDS refers only to the specific material designated and does not relate to any process or use involving other materials. This information is based on data believed to be reliable, and the Product is intended to be used in a manner that is customary and reasonably foreseeable. Since actual use and handling are beyond our control, no warranty, express or implied, is made and no liability is assumed by Seatex Corporation in connection with the use of this information.